

Applications:

Metal and Stone Sawing/Grinding
Wood Products Manufacturing
Printing Industry
Auto Body Shops and Fiberglass Manufacturing
Fabric Processing and Printing



RD-211-QL



RD-337-QL



RD-455-QL

Features:

Portable Design with 3 Phase TEFC Induction Motors
Polyester Fabric Filters with Manual Shaker
Phenolic Cartridge Filter with Pulse-Jet Cleaning Optional
Easy Removal of Dust Bucket
Choice of Standard or “Hi-Flow” Blower Package
HEPA Filtration Available on All Models

For Further Information Please Contact:

RYVAC Engineering Company
13841 Oaks Avenue
Chino, CA 91710 USA

Sales: 818-241-7436
Mfg: 909-627-2150

Fax 818-241-8712
Fax: 909-627-8440

eMail: gtw@ryvac.com

Visit our WWW site at: www.ryvac.com

Model:	RD-211-QL	RD-337-QL	RD-455-QL
Input Voltage:	230/460 VAC	230/460 VAC	230/460 VAC
Power Consumption:	1.1 KW (1.5 HP)	3.7 KW (5 HP)	5.5 KW (7.5 HP)
Amperage:	4.2/2.1 Amps Max	12.6/36.3 Amps Max	19.2/9.6 Amps Max
Power Cable:	10 Ft, 18 AWG	10 Ft, 16 AWG	10 Ft, 14 AWG
Maximum Airflow:	1200 cfm	2400 cfm	3100 cfm
Max Static Pressure:	9" H ₂ O	12" H ₂ O	14" H ₂ O
Dust Capacity:	5 Gallons	15 Gallons	27 Gallons
Size(W x L x H):	23" x 23" x 53"	29" x 29" x 59"	35" x 35" x 68"
Weight:	175 lbs	345 lbs	495 lbs
Noise Level:	80 dBA	83 dBA	85 dBA
Hose Diameter:	6"	8"	10"
1st Filter:	50 sq ft, Polyester	76 sq ft, Polyester	135 sq ft, Polyester
2nd Filter:	Optional, HEPA	Optional, HEPA	Optional, HEPA

RYVAC Dust Collectors Performance

