

Applications:

Metal Grinding and Polishing
Toxic Dusts and Powders
Welding and Finishing Booths
All Airborne Dust-Producing Industrial Processes



Features:

Polyester Fabric plus Certified HEPA Filtration
5 HP (Three-Phase) or 3 HP (220 VAC Single-Phase) Power
2000 cfm, Quiet Continuous Duty Operation

For Further Information Please Contact:

RYVAC Engineering Company
13841 Oaks Avenue
Chino, CA 91710 USA

Sales: 818-241-7436
Mfg: 909-627-2150

Fax 818-241-8712
Fax: 909-627-8440

eMail: gtw@ryvac.com

Visit our WWW site at: www.ryvac.com

Model:

RD-337-QLH

RD-338-ELH

Input Voltage:	230/460 VAC (Three Phase)	220 VAC (Single Phase)
Power Consumption:	3.7 KW (5.0 HP)	3.8 KW (3 HP)
Amperage:	12.8/6.4 Amps Max	18.4 Amps Max
Power Cable:	10 Ft, 16 AWG	10 Ft, 12 AWG
Maximum Airflow:	2000 cfm	2000 cfm
Max Static Pressure:	12" H2O	9" H2O
Dust Capacity:	15 Gallons	15 Gallons
Size(W x L x H):	29" x 29" x 74"	29" x 29" x 74"
Weight:	340 lbs	375 lbs
Noise Level:	83 dBa	81 dBa
Hose Diameter:	8"	8"
1st Filter:	76 sq ft, Polyester	76 sq ft, Polyester
2nd Filter:	HEPA, 24x24x12	HEPA, 24x24x12

RYVAC Dust Collectors Performance

