

### Applications:

Heavy-Duty Cleanup for Machine Shops, Metal  
Fabrication and Semiconductor Manufacturing  
Food Processing, Printing Industry and Textile Mills  
Central Vac Systems  
Wet or Dry General Industrial Cleanup



**RP-115-QLT**



**RP-426-QLT**



**RP-546-QLT**

### Features:

Portable Design with 3 Phase TEFC Induction Motor  
Dual Filtration with Cyclone Pretank  
Polyester Fabric Filters with Shaker  
Full Accessory Kit Included  
Easy Removal of Dust Bucket  
HEPA Filtration Available on All Models

For Further Information Please Contact:

**RYVAC Engineering Company**  
3641 Walnut Avenue  
Chino, CA 91710 USA

**Sales: 818-241-7436**  
**Mfg: 909-627-2150**

**Fax 818-241-8712**  
**Fax: 909-627-8440**

**eMail: [gtw@ryvac.com](mailto:gtw@ryvac.com)**

**Visit our WWW site at: [www.ryvac.com](http://www.ryvac.com)**

Model:	RP-115-QLT	RP-426-QLT	RP-546-QLT
Input Voltage:	230/460 VAC	230/460 VAC	230/460 VAC
Power Consumption:	1.5 KW (2 HP)	2.55 KW (3.4 HP)	4.6 KW (6.2 HP)
Amperage:	5.8/2.9 Amps Max	10/5 Amps Max	17.2/8.6 Amps Max
Power Cable:	30 Ft, 18 AWG	30 Ft, 16/18 AWG	30 Ft, 14/16 AWG
Maximum Airflow:	95 cfm	150 cfm	225 cfm
Max Static Pressure:	83" H <sub>2</sub> O	105" H <sub>2</sub> O	130" H <sub>2</sub> O
Dust Capacity:	10 Gallons	12 Gallons	30 Gallons
Size(W x L x H):	19" x 40" x 37"	19" x 40" x 42"	21" x 45" x 50"
Weight:	150 lbs	200 lbs	290 lbs
Noise Level:	70 dBA	73 dBA	76 dBA
Hose Diameter:	1-1/2" or 2"	2"	2"
1st Filter:	11 sq ft, Polyester	17 sq ft, Polyester	29 sq ft, Polyester
2nd Filter:	Optional, HEPA	Optional, HEPA	Optional, HEPA

