


Applications:

Heavy-Duty Cleanup for Machine Shops, Metal
Fabrication and Semiconductor Manufacturing
Food Processing, Printing Industry and Textile Mills
Central Vac Systems
Wet or Dry General Industrial Cleanup
115 Model Has Open-Frame Design, PCB Industry



RP-115-QC



RP-426-QLT



RP-546-QLT

Features:

Portable Design with 3 Phase TEFC Induction Motor
Dual Filtration with Cyclone Pretank
Polyester Fabric Filters with Shaker (Cartridge in 115)
Full Accessory Kit Included
Easy Removal of Dust Bucket
HEPA Filtration Available on All Models

For Further Information Please Contact:

RYVAC Engineering Company
13841 Oaks Avenue
Chino, CA 91710 USA

Sales: 818-241-7436
Mfg: 909-627-2150

Fax 818-241-8712
Fax: 909-627-8440

eMail: gtw@ryvac.com

Visit our WWW site at: www.ryvac.com

Model:	RP-115-QC	RP-426-QLT	RP-546-QLT
Input Voltage:	230/460 VAC	230/460 VAC	230/460 VAC
Power Consumption:	1.5 KW (2 HP)	2.55 KW (3.4 HP)	4.6 KW (6.2 HP)
Amperage:	5.8/2.9 Amps Max	10/5 Amps Max	17.2/8.6 Amps Max
Power Cable:	5 Ft, 18 AWG	30 Ft, 16/18 AWG	30 Ft, 14/16 AWG
Maximum Airflow:	95 cfm	150 cfm	225 cfm
Max Static Pressure:	83" H ₂ O	105" H ₂ O	130" H ₂ O
Dust Capacity:	2 Gallons	12 Gallons	30 Gallons
Size(W x L x H):	19" x 18" x 25"	19" x 40" x 42"	21" x 45" x 50"
Weight:	36 lbs	200 lbs	290 lbs
Noise Level:	68 dBA	73 dBA	76 dBA
Hose Diameter:	2"	2"	2"
1st Filter:	32 sq ft, Phenolic	17 sq ft, Polyester	29 sq ft, Polyester
2nd Filter:	Optional, HEPA	Optional, HEPA	Optional, HEPA

