

Applications:

Economical Vacuums for General Dry Cleanup
Machine Shops and Metal Fabricators
Auto Body and Fiberglass Manufacturing
Foods Processing and Pottery Industry
Car and Truck Care



RE-115-AL



RE-217-AL



RE-924-AL

Features:

Twin Motors, 115 or 230 VAC Power Input
Portable, Lightweight and Ergonomic Design
Polyester Fabric Filters with Shaker
Full Accessory Kit Included
Easy Removal of Dust Bucket
HEPA Filtration Available on All Models

For Further Information Please Contact:

RYVAC Engineering Company
13841 Oaks Avenue
Chino, CA 91710 USA

Sales: 818-241-7436
Mfg: 909-627-2150

Fax 818-241-8712
Fax: 909-627-8440

eMail: gtw@ryvac.com

Visit our WWW site at: www.ryvac.com

Model:	RE-115-AL	RE-217-AL	RE-924-AC
Input Voltage:	115/230 VAC	115/230 VAC	115/230 VAC
Power Consumption:	1.5 KW (2 HP)	1.7 KW (2.3 HP)	2.4 KW (3.2 HP)
Amperage:	13.5/6.8 Amps Max	15/7.5 Amps Max	20/10 Amps Max
Power Cable:	30 Ft, 16/18 AWG	30 Ft, 14/18 AWG	30 Ft, 12/16 AWG
Maximum Airflow:	160 cfm	180 cfm	200 cfm
Max Static Pressure:	67" H ₂ O	80" H ₂ O	100" H ₂ O
Dust Capacity:	5 Gallons	15 Gallons	55 Gallons
Size(W x L x H):	17" x 21" x 32"	21" x 26" x 35"	25" x 25" x 50"
Weight:	45 lbs	65 lbs	85 lbs
Noise Level:	75 dBA	76 dBA	78 dBA
Hose Diameter:	1-1/2" or 2"	2"	2"
1st Filter:	11 sq ft, Polyester	19 sq ft, Polyester	32 sq ft, Phenolic
2nd Filter:	Optional, HEPA	Optional, HEPA	Optional, HEPA

